







SMALL TIDE AND WAVE LOGGERS

MEASURE MORE,
DEPLOY LONGER,
DOWNLOAD FASTER



The RBRsolo³ is RBR's most compact, lightweight, and versatile single channel logger. RBRsolo³ D|tide and RBRsolo³ D|wave loggers offer flexible measurement schedules, long wave burst samples, expanded memory and power for extended deployments and faster download of large data files.

FEATURES

					
Flexible tide averaging	Low frequency wave detection	16Hz sampling	USB-C download	Intermittent & continuous burst	Cabled RBRcoda ³ variant available

Small tide and wave loggers are available in the following configurations:

- ▶ RBRsolo³ D|tide16 pressure logger with tidal averaging, up to 16Hz continuous sampling
- ▶ RBRsolo³ D|wave16 pressure logger with intermittent and continuous wave burst and tidal averaging, up to 16Hz
- ▶ RBRduet³ T.D|tide16 temperature and tide recorder, up to 16Hz averaging
- ▶ RBRduet³ T.D|wave16 temperature, tide and wave recorder, up to 16Hz burst & continuous sampling

The single channel tide and wave loggers provide the ease and flexibility to establish the best sampling regime for your measurements. Both loggers take averages of the pressure readings over longer periods of time and at rates up to 16Hz to provide accurate tide level readings. The wave recorder bursts continuously or intermittently making it easier to measure infrequent phenomena such as boat wakes. The large number of burst samples makes low frequency waves easier to detect. A dedicated desiccant holder makes it simple to replace desiccant before each deployment.

Dataset export to Matlab, Excel, OceanDataView®, or text files makes post processing with your own algorithms effortless. The included Ruskin software performs wave analysis, to provide basic information about the wave composition (e.g. wave energy, $H_{1/3}$, $T_{1/3}$, T_{ave} and H_{ave}).

SMALL TIDE AND WAVE LOGGERS

MEASURE MORE,
DEPLOY LONGER,
DOWNLOAD
FASTER



Flexible tide averaging



Low frequency wave detection



16Hz sampling



USB-C



Intermittent and continuous burst ability



Cabled RBRcoda³ variant available



RBR Ltd

95 Hines Road
Ottawa, Ontario
Canada K2K 2M5

+1 613 599 8900
info@rbr-global.com
rbr-global.com

Specifications

Physical

Power:	Any AA battery
Communication:	USB-C
Clock drift:	±60 seconds/year
Diameter:	25.4mm
Length:	210mm
Weight(air):	125g
Storage:	~60M readings

Pressure

Range:	20/50
Accuracy:	±0.05% FS (full scale)
Resolution:	0.001% FS
Time constant:	<0.01
Typical stability:	0.1% FS per year

RBRsolo³ D|tide16

Sampling rate:	24hr to 1s and 2, 4, 8, or 16Hz
Averaging duration:	1s to 24h
Averaging interval:	1s to 24h

RBRsolo³ D|wave16*

Sampling rate:	24hr to 1s and 2, 4, 8, or 16Hz
Burst (samples):	512 to 32768 (powers of 2)
Burst interval:	1s to 24hr

*Tide values are the average of the burst readings

RBRduet³ T.D|tide16

Sampling rate:	24hr to 1s and 2, 4, 8, or 16Hz
Averaging duration:	1s to 24h
Averaging interval:	1s to 24h

RBRduet³ T.D|wave16*

Sampling rate:	24hr to 1s and 2, 4, 8, or 16Hz
Burst (samples):	512 to 32768 (powers of 2)
Burst interval:	1s to 24hr

*Tide values are the average of the burst readings

Realtime variant

Cabled realtime variant available as the RBRcoda³.

Deep variant

Explore up to 10km deep with the RBRsolo³ T|deep. Details available on the RBRsolo³ and RBRduet³|deep datasheet.

